

(8182)63-90-72
 (7172)727-132
 (8512)99-46-04
 (3852)73-04-60
 (4722)40-23-64
 (4832)59-03-52
 (423)249-28-31
 (844)278-03-48
 (8172)26-41-59
 (473)204-51-73
 (343)384-55-89
 (4932)77-34-06


(3412)26-03-58
 (395)279-98-46
 (843)206-01-48
 (4012)72-03-81
 (4842)92-23-67
 (3842)65-04-62
 (8332)68-02-04
 (861)203-40-90
 (391)204-63-61
 (4712)77-13-04
 (4742)52-20-81
 (996)312-96-26-47



(3519)55-03-13
 (495)268-04-70
 (8152)59-64-93
 (8552)20-53-41
 (831)429-08-12
 (3843)20-46-81
 (383)227-86-73
 (3812)21-46-40
 (4862)44-53-42
 (3532)37-68-04
 (8412)22-31-16
 (772)734-952-31

(342)205-81-47
 - - (863)308-18-15
 (4912)46-61-64
 (846)206-03-16
 - (812)309-46-40
 (845)249-38-78
 (8692)22-31-93
 (3652)67-13-56
 (4812)29-41-54
 (862)225-72-31
 (8652)20-65-13
 (495)268-04-70

(3462)77-98-35
 (4822)63-31-35
 (3822)98-41-53
 (4872)74-02-29
 (3452)66-21-18
 (8422)24-23-59
 (347)229-48-12
 (4212)92-98-04
 (351)202-03-61
 (8202)49-02-64
 (4852)69-52-93

cvn@nt-rt.ru || <https://civintec.nt-rt.ru/>
 - CIVINTEC

Family	Part No.	Type	Description	Unit Price
CN890A			Size: 230*160*45mm Type: 13.56MHz terminal for indoor use	
CN890A	CN890001	CN890A-T-M	CN890A-T-M uTouch X - Android5.1 OS Intelligent Terminal 7" High Resolution Touch Screen With 5MP Autofocus Camera Protocol Support: 13.56MHz ISO14443A/B 1-4,ISO15693,ISO18092 P2P NFC,ISO7816 Contactless Card Supported: Mifare® Classic, Mifare® Plus,DESFire® EV1,ultralight® C,NFC tag Secure Access Module: 1XSAM Communication Interface: TCP/IP, RS232/RS485(OSDP),Wiegand, GPIO,USB Indoor Use, 9-24VDC	on request
SDK		CN890(F)A SDK	SDK for CN890(F)A-XX-XX-XX Android embedded software development	on request

Flush Mount Touch Reader			Size: 165*84*24.5mm Type: Outdoor flush mount use System: Linux	
CT5	CT500001	CT5-M-F	CRYSTAL CT5-M-F Smart 3.5" Touch Screen Reader, Linux System Multi-Protocol Support: ISO14443A/B, ISO18092 NFC, ISO7816 SAM, BLE Contactless Card Supported: Mifare® Classic, JCOP, Mifare® plus, Desfire® EV1/EV2, NFC Tags Secure Access Module: Yes, 1* SAM slot Smart Phone Supported: Yes (NFC, BLE) Communication Interface: BLE/RS485(OSDP)/Wiegand/C&D, ABA, GPIO Input Devices: Touch screen Power Supply: +9-30VDC Installation requirements: Flush Mount & Connector Out door use -20°C ~ +60°C with heater, IP65, electric epoxy potted	on request
CT5CK5CT9	CTK00005	HTP-CTK	1. Power supply 1pc 2. TCP/IP network cable 1pc (CT only) 3. CC-Debugger cable+USB cable 1pc 4. Software upgrade cable 1pc (CT only) 5. Wires 1pc 6. Testing Cards, incl. Mifare S50 ISO white PVC glossy card 1pc EM4001 ISO white PVC glossy Card 1pc 7. CTK Configuration tools, incl. - Configcard software - Authentication card software (customer) - CTK Authentication Card 1pc - CTK Change Authentication Card 1pc - CTK Configuration Card 2pcs - CTK OSDP Installation Mode Card 1pc (CT5/CK5 only) - Connection cable SC9910-BK RS485=>USB 1pc 8. Upgrade cable USB=>UART 1pc (CK only)	on request
CRYSTAL	ACCESS CONTROL TOUCH TERMINAL			
Flush Mount Touch Terminal			Size: 165*84*24.5mm Type: Outdoor flush mount use System: Linux	

CT9	CT900001	CT9-MT-F	<p>CRYSTAL CT9-MT-F Smart 3.5" Touch Screen Terminal, Linux System Multi-Protocol Support: ISO14443A/B,ISO18092 NFC,ISO7816 SAM,BLE Contactless Card Supported: Mifare® Classic, JCOP,Mifare® plus,Desfire® EV1/EV2,NFC Tags Secure Access Module: Yes, 1* SAM slot Smart Phone Supported: Yes(NFC,BLE) Communication Interface: TCP/IP/RS485/BLE/Wiegand/GPIO Input Devices: Touch screen Output Control: 1xRelay Working Mode:On Line/Off Line Power Supply: +9-30VDC Installation requirements: Flush Mount&Connector Out door use with heater-20°C-+60°C, IP65,electric epoxy potted</p>	on request
CRYSTAL CT9 Terminal SDK Software				
CT9	CTS90001	CT9 Terminal SDK Software	SDK for CT9-M(E)T-X software development	on request
Hardware Testing & Upgrading Tool				
	CTK00005	HTP-CTK	<ol style="list-style-type: none"> 1. Power supply 1pc 2. TCP/IP network cable 1pc (CT only) 3. CC-Debugger cable+USB cable 1pc 4. Software upgrade cable 1pc (CT only) 5. Wires 1pc 6. Testing Cards, incl. Mifare S50 ISO white PVC glossy card 1pc EM4001 ISO white PVC glossy Card 1pc 7. CTK Configuration tools, incl. - Configcard software - Authentication card software (customer) - CTK Authentication Card 1pc - CTK Change Authentication Card 1pc - CTK Configuration Card 2pcs - CTK OSDP Installation Mode Card 1pc(CT5/CK5 only) - Connection cable SC9910-BK RS485=>USB 1pc 8. Upgrade cable USB=>UART 1pc (CK only) 	on request
CN56X0B			<p>Size: 126*68*19mm</p> <p>Type: outdoor 0C housing</p>	

CN56X0B	CN5600003	CN5600B-T-0C	CN5600B-T-0C Access Control Door Reade Multi-function:ISO14443A Mifare secure sector Communications: TCP/IP,Wiegand 26 (default),34,42,50,58/C&D8,10(3byte/5byte),ABA1/2 Output Control: Relay External control: C_Red LED、 C_Green LED、 C_Buzzer Power supply: +9-24VDC Installation requirements: Connector Out door use,IP65,electric epoxy potted	on request
CN56X0B	CN5600005	CN5610B-2-0C	CN5610B-2-0C Access Control Door Reader Multi-function: ISO14443A Mifare, Mifare plus, Communications: RS232/Wiegand 26 (default),34,42,50,58/C&D8,10(3byte/5byte),ABA1/2 External control: C_Red LED、 C_Green LED、 C_Buzzer Power supply: +9-24VDC Installation: Connector Out door use, IP65, electric epoxy potted	on request
CN56X0B	CN5600006	CN5610B-4-0C	CN5610B-4-0C : Access Control Door Reade Multi-function:ISO14443A Mifare, Mifare plus, Communications: RS485/Wiegand 26 (default),34,42,50,58/C&D8,10(3byte/5byte),ABA1/2 External control: C_Red LED、 C_Green LED、 C_Buzzer Power supply: +9-24VDC Installation requirements: Connector Out door use,IP65,electric epoxy potted	on request
CN56X0B	CN5600026	CN5650B-2-0C	CN5650B-2-0C Access Control Door Reader, Multi-function:ISO14443A, Mifare, Mifare plus,DESFire EV1,Felica card,ISO18092 NFC P&P/T2T/T4T Communications: RS232/Wiegand 26 (default)34,42,50,58/C&D8,10(3byte/5byte),ABA1/2 External control: C_Red LED、 C_Green LED、 C_Buzzer Power supply: +9-24VDC Installation requirements: Connector Out door use,IP65,electric epoxy potted	on request

CN56X0B	CN5600028	CN5650B-4-0C	CN5650B-4-0C Access Control Door Reader, Multi-function:ISO14443A Mifare, Mifare plus, DESFire EV1, Felica card, ISO18092 NFC P&P/T2T/T4T Communications: RS485/Wiegand 26 (default),34,42,50,58/C&D8,10(3byte/5byte),ABA1/2 External control: C_Red LED、C_Green LED、C_Buzzer Power supply: +9-24VDC Installation requirements: Connector Out door use,IP65,electric epoxy potted	on request
CN56X0B	CN5600024	CN5650B-T-0C	CN5650B-T-0C Access Control Door Reader, Multi-function:ISO14443A Mifare, Mifare plus, DESFire EV1, Felica card, ISO 18092 NFC P&P/T2T/T4T Communications: TCP/IP,Wiegand 26 (default),34,42,50,58/C&D8,10(3byte/5byte),ABA1/2 Output Control: Relay External control: C_Red LED、C_Green LED、C_Buzzer Power supply: +9-24VDC Installation requirements: Connector Out door use,IP65,electric epoxy potted	on request
CN6XX			Size: 116*67*14mm Type: USB / RS232 Interface	
CN6XX(S)-X	CN670003	CN670-U	CN670-U 13.56MHz R/W Desktop Reader ISO14443A 1-4 Mifare,Mifare plus,Desfire EV1,ISO14443B and ISO18092 NFC Felica Interface: USB Power supply: 5V DC Size: 116*67*14mm	on request
SDK			SDK-----Software Development Kit	
SDK	CVSD0018	CNReader SDK	CNReader SDK For CN3XX(S)(T)-X, CN6XX(S)-X	on request
SDK		CN56X0B SDK	CN56X0B SDK for CN56X0B reader software development	on request
CH3X(S)(Z)-X	13.56MHz R/W OEM READER MODULE			
CH3X(S)(Z)-X			Size: 32mm*28mm Type: 13.56MHz R/W mini Reader Module	

CH31	CH310001	CH31-X	CH31-X 13.56MHz R/W mini Reader Module,Low Power Consumption ISO14443A 1-4 Mifare,Mifare plus,Desfire EV1,Ultralight,Ultralight C, ISO14443B,ISO15693,Felica and ISO18092 NFC Interface: USB/TTL/SPI/Wiegand26,32,32e,34,40,42,50,56,58C&D/ABA1,2 Antenna: works with single external antenna Power supply: 3.3V DC	on request
SDK			SDK-----Software Development Kit	
SDK		CH3X(S)-X SDK	CH3X(S)-X SDK For CH3X(S)-X	on request

(8182)63-90-72
(7172)727-132
(8512)99-46-04
(3852)73-04-60
(4722)40-23-64
(4832)59-03-52
(423)249-28-31
(844)278-03-48
(8172)26-41-59
(473)204-51-73
(343)384-55-89
(4932)77-34-06

(3412)26-03-58
(395)279-98-46
(843)206-01-48
(4012)72-03-81
(4842)92-23-67
(3842)65-04-62
(8332)68-02-04
(861)203-40-90
(391)204-63-61
(4712)77-13-04
(4742)52-20-81
(996)312-96-26-47

(3519)55-03-13
(495)268-04-70
(8152)59-64-93
(8552)20-53-41
(831)429-08-12
(3843)20-46-81
(383)227-86-73
(3812)21-46-40
(4862)44-53-42
(3532)37-68-04
(8412)22-31-16
(772)734-952-31

(342)205-81-47
- - (863)308-18-15
(4912)46-61-64
(846)206-03-16
- (812)309-46-40
(845)249-38-78
(8692)22-31-93
(3652)67-13-56
(4812)29-41-54
(862)225-72-31
(8652)20-65-13
(495)268-04-70

(3462)77-98-35
(4822)63-31-35
(3822)98-41-53
(4872)74-02-29
(3452)66-21-18
(8422)24-23-59
(347)229-48-12
(4212)92-98-04
(351)202-03-61
(8202)49-02-64
(4852)69-52-93